35mm Camera

Vivitar®
We make it easy™

V3800N

New for 2001!

CAMERA SPECIFICATIONS

Type	*35mm SLR manual camera*
Lens Mount	*Quick release "K" type bayonet mount*
Shutter	*Vertical travel, metal focal plane shutter*
Shutter Speeds	*Manually set from B to 1/2000*
Flash Synchronization	*Hot shoe with X-contact synchronized at 1/125 or slower*
Viewfinder	*Fixed, eye-level pentaprism with 92% field of view*
Viewfinder Displays	*TTL Center weighted exposure metering: Red + over exposure, Green o correct exposure, Red -- under exposure*
Film Advance	*Single frame advance, thumb lever action with 130° throw and 20° stand-off. Safety mechanism prevents double frame advance or double exposures. Manual rewind.*
Viewfinder	*Bright viewfinder with split image focusing and three LED display*
Self Timer	*10 Second delay*
Mount	*Pentax K bayonet*
Power Source	*Two 1.5 volt alkaline (LR44) or Silver batteries (SR44)*
Dimensions	*5.4 x 3.5 x 2.3 inches (138 x 88 x 58mm)*
Weight	*13 oz. (370 grams)*
Warranty	*1 Year*

LENS SPECIFICATIONS

Type	*28-70mm f/3.4-4.8 lens*
Lens Coating	*Multicoated*
Accessory Size	*52mm*
Warranty	*Five years*

Specifications subject to change without notice © 2000 Vivitar Corporation

Stock Numbers *SLR W/28-70mm & Case* *59890*
UPC Code *019643-59890-4*

PRELIMINARY

Features:

- Affordable SLR camera with a 28-70mm zoom lens
- Easy to use manual SLR camera ideal for the first-time SLR user
- Includes 28-70mm f/3.4-4.8 lens
- Depth of field preview
- Multiple exposure capability
- Bright viewfinder with split image focusing and three-LED display
- Hot shoe with x-contact for flash photography, synchronized at 1/125 second or slower
- Film speed range: ISO 25 to 3200
- Accurate center-weighted, TTL metering system
- Self timer with 10 second delay

V3800N

VIVITAR Corporation
1280 Rancho Conejo Blvd.
Newbury Park, CA 91320
(805)498-7008